


AC2315



AS-Interface dual sensor for pneumatic valve actuators

DUAL SENSOR T4 2SI M12



Product characteristics		
Electrical design		AS-i
Sensing range	[mm]	4
Housing		rectangular
Dimensions	[mm]	55 x 60 x 35
Application		
Application		position sensor for valve actuators; actuator control
Electrical data		
Operating voltage	[V]	26.5...31.6 DC; ("supply class 2" to cULus)
Current consumption	[mA]	< 40
Outputs		
Electrical design		AS-i
Detection zone		
Sensing range	[mm]	4
Operating conditions		
Ambient temperature	[°C]	-20...70

AC2315



AS-Interface dual sensor for pneumatic valve actuators

DUAL SENSOR T4 2SI M12


Protection		IP 67	
Tests / approvals			
EMC		EN 50295	
		EN 61000-6-2	
MTTF	[years]	924	
AS-i classification			
AS-i version		2.1	
Extended addressing mode		yes	
AS-i I/O configuration		[hex]	0
AS-i ID code		[hex]	A.F
AS-i certificate		74901	
Mechanical data			
Weight		[g]	149.5
Housing		rectangular	
Mounting		non-flush mountable	
Dimensions		[mm]	55 x 60 x 35
Materials		housing: PBT	
Displays / operating elements			
Display		switching status	2 x LED, yellow
Accessories			
Items supplied		Reinforcement bracket: 1 x (39,5 x 17,5 x 1 mm), E11310	
		socket head screws: 2 x (M5 x 35 mm)	
		washers: 2	
Remarks			
Pack quantity		1 pcs.	
Electrical connection			
Electrical connection - plug			
Connector: 1 x M12; coding: A; Locking: stainless steel (303/1.4305)			
			



AS-Interface dual sensor for pneumatic valve actuators

DUAL SENSOR T4 2SI M12

Connection



Electrical connection

1	AS-i +
3	AS-i -